

407 Route 125
Brentwood, NH

If using GPS Please
Use #407 Calef Highway

Tel. 603-679-1230

Email: retail@highlandhardwoods.com

www.highlandhardwoods.com

Hours:

Monday– Friday
8:00 am - 4:30 pm

Saturdays
8:00 am - 1:00 pm



Dubeau grade: Strong color variation
Mineral streaks, sound knots
Mix of s & b and #1 common grades
25 Year finish wear-through limited warranty
Tavern Grade: All color variations accepted
Worm holes & surface holes/open & sound knots. Machine marks & short planks
Allow losses of at least 10% No Warranty
Bistro Grade: Natural look with frequent species characteristics. Moderate to pronounced color variation. With sound & filled knots & Mineral streaks. Medium to long average planks.

DUBEAU FLOORING

Prices Effective: 1/01/18

2 1/4" & 3 1/4" - 20 sq ft /bdl 4 1/4" -17 sq ft /bdl	Grade	2-1/4	3-1/4	4-1/4
Red Oak natural	Dubeau	5.19	5.70	
Red Oak natural	Tavern		3.25	
*Red Oak Stained	Dubeau	5.59	6.10	
*Red Oak Stained	Wire Brushed		6.39	6.65
Red Oak Castagna	Tavern			3.25
Maple natural	Dubeau		5.45	
Maple natural	Tavern		3.25	
Maple Castagna	Bistro			5.35
*Maple natural	Select & Better		7.29	
Maple Montpellier	Dubeau		5.45	
*Maple Stains	Dubeau		5.85	
*Maple Antique Bronze	ultramatte		6.10	6.55
*Maple Nickel & Sisel	ultramatte			6.90
*Yellow Birch natural	Dubeau		5.65	
Yellow Birch Mineral	Ultramatte		5.99	
*Yellow Birch Stains	Dubeau		5.35	
*Red Birch natural	ultramatte		6.10	
Red Birch natural	Supermatte		5.75	

Flooring With *Symbol Are Special Orders / No Cancellations or Returns. 75% Deposit Required

Ordering & Return Policy: All sales subject to availability-
All sales require minimum 25% deposit- Orders must be picked up within 30 days.
If not picked up customer will be refunded & lose sale price.
All returns must be un-opened, in original condition, and be made within 45 days
-from either purchase date or product arrival date to highland hardwoods.
All returns must be accompanied w/ sales receipt-
(Special orders Non Returnable)
Prices subject to change without notice.
NOTE: Allow stock to acclimate 1-2 weeks prior to installation
Allow minimum 5% waste for cutting.